

Door Closer Models: HD7016 FT, FTH Flush Transom Track Installation (Push Side Mount) with Plates BP70T, BP70TFC Drilling Instructions

For online instructions, assistance or warranty information:
Call 1-800-392-5209 or visit <https://dhwsupport.dormakaba.com/hc/en-us>

NOTES:

1. DO NOT SCALE DRAWING.
2. DIMENSIONS ARE IN INCHES/(MM).
3. LEFT HAND DOOR SHOWN.
4. CAUTION: SEX NUTS ARE REQUIRED FOR ATTACHMENT OF COMPONENTS TO UNREINFORCED DOORS AND TO WOOD OR PLASTIC FACED COMPOSITE TYPE FIRE DOORS, UNLESS AN ALTERNATIVE METHOD IS IDENTIFIED IN THE INDIVIDUAL DOOR MANUFACTURER'S LISTINGS.
5. DPK FASTENERS FOR STEEL DOOR & FRAME ONLY.
6. MAX. OPENING IS 140°.

ANGLE OF OPENING	DIM. "C" PLATE	DIM. "B" TRACK	HOLD OPEN RANGE
85°	5-9/16" (141)	7-1/8" (181)	30° - 82°
90°	5-1/16" (129)	6-13/16" (173)	30° - 87°
110°	4-1/16" (103)	5-1/2" (140)	30° - 105°
140°	3-1/8" (79)	4-3/4" (121)	30° - 125°

