

RHR SHOWN  
LHR OPPOSITE

**ES105 LOCATION**  
**DOOR MANUFACTURER**  
**MUST PROVIDE 3/8" MIN.**  
**RACEWAY THROUGH DOOR**  
**TO ALLOW FOR ELECTRICAL**  
**WIRES, BETWEEN DOOR**  
**EDGE AND OUTSIDE TRIM.**

**OUTSIDE FACE ONLY**  
**FOR LFSF TRIM**

Ⓢ **VERTICAL**  
**REF. 2 3/4"**  
**(70 mm)**

**EDGE OF DOOR**

**1 1/2"**  
**(38 mm)**

**3/4"**  
**(19 mm)**

**3/8" (9 mm) DIA.**  
**HOLE THRU DOOR.**  
**(4) PLACES**

**3 3/4"**  
**(95 mm)**

**7 1/2"**  
**(190 mm)**

**40 5/16"**  
**(1024 mm)**

**OUTSIDE FACE**  
**ONLY FOR LFSC TRIM**

**FINISHED FLOOR LINE OR TOP OF THRESHOLD**

NOTES:

1. SEE MASTER SHEET #T-0001 FOR SUGGESTED DOOR REINFORCEMENT.
2. SEE ADDITIONAL TRIM TEMPLATE WHEN REQUIRED.

REV. No. 1

REVISION:

DATE: 4-8-09



YR09 LFSC OR LFSF FUNCTION  
ADDITIONAL RACEWAY PREP

TEMPLATE NUMBER

T-9021 ①