










All-in-One Strikes
BES-F2164 (Fire-Rated/Fail-Secure)
BES-2364 (Fail-Safe)



These versatile All-in-One Strikes are designed for offset and centerline latch entry.

With 1500 pounds of holding force, BEST All-in-One Strikes combine strength and convenience in a versatile, easy to install design.


With the sawtooth adjustment locator, installers can adjust the strike to align with a wide variety of mortise locks with offset latches eliminating the need to order special faceplates making BEST All-in-One Strikes versatile and easy to install.

-  **Energy**
375mA¹ Field-selectable
12/24VDC, 12-24VAC²
-  **Fire-Rated**
Optional 3-hour
Model Available³
-  **Strength**
1500lb Static
70ft-lb Dynamic
-  **Latch Monitor**
Plug-in Accessory
Available
-  **Endurance**
500,000 Cycles
-  **Warranty**
Five-year (Limited)
-  **Mode**
Fail-Secure and Fail-Safe

All-in-One Strikes

Versatile, convenient and easy to install.

These electric strikes—featuring an adjustable deadbolt keeper and deadlatch ramp—combine strength and convenience in an attractive, sleek and easy-to-install design.



Saw-tooth
Adjustment Locator



Deadbolt Plug

Product specifications

| | |
|----------------------|--|
| Faceplate | 1-1/4" (32mm) W x 4-7/8" H (124mm) |
| Insert depth | 1-3/4"D (45mm) |
| Door lock type | Mortise, cylindrical and mortise exit device |
| Frame type | Hollow metal, aluminum and wood |
| Latch projection | 1/2" (12.7mm) to 3/4" (19mm) |
| Connectors | Plug-in wire |
| Handing | Non-handed |
| Optional accessories | BES-F2LM Latch monitor plug-in kit (2A @ 24VDC) |
| Finishes | 32D Brushed Stainless Steel |
| Warranty | Five-year limited |
| Certifications | UL 294 Listed for Access Control Unit Accessory (6th Edition) UL 1034 burglary-resistant Listed UL 10C, 3-hour fire-rating Listed ³ CAN/ULC S104, 3-hour fire-rating Listed ³ Certified to ANSI/BHMA standard A156.31, Grade 1, endurance 500,000 cycles |

Features

BEST All-in-One Strikes

- **Modular design:** compatible with most locks; no special faceplates required; non-handed
- **Adjustable:** deadbolt keeper and deadlatch ramp—up to 5/16" of strike for precise alignment with lockset; keeper shims for horizontal adjustment¹—1/16" (1.5mm) and 1/8" (3mm)—for up to 1/8" (3mm)
- **Run cool operation:** solenoid design prevents keeper from heating up
- **Heavy-duty construction:** stainless steel with brushed stainless steel finish (32D)
- **Holding force:** up to 1500lbf (680kgf)
- **Easy installation:** non-handed; fits HES 1006 (1003) frame cutout (hollow metal)
- **Secure:** accommodates up to 3/4" latch projection; up to 1" deadbolt (night-latch function only, bolt will not release)
- **Included:** faceplate, trim plate and anti-tamper security screws for centerline latch entry; star and security driver bit; and, adhesive paper template
- **Field selectable voltage input:** accommodates 12 or 24VDC and 12 to 24VAC
- **Low current draw:** 0.19 Amps @24VDC; plug-in wire connector
- **Patents:** US patent 9,580,935 and Canadian patent 2,850,072
- **Warranty:** five-year limited


| Model | Mode | Volts | Duty | Sound | Amps | Ohms* |
|-----------|-------------|----------|--------------|--------|-------------|-------|
| BES-F2164 | Fail Secure | 12VDC | Continuous | Silent | 0.375 | 37 |
| | | 24VDC | | | | |
| | | 12-24VDC | Intermittent | Buzz | 0.280-0.565 | 37 |
| BES-2364 | Fail Safe | 12VDC | Continuous | Silent | 0.375 | 37 |
| | | 24VDC | | | | |

Intermittent Duty: Energized less than one minute with duty ratio 1:5

Continuous Duty: Energized one minute or more

*Nominal resistance at +25°C ± 7% tolerance


Frame Type



Hollow Metal



Aluminum



Wood

Door Lock Type



Mortise



Cylindrical



Exit Device

Choose BEST All-in-One Strikes
for a solution that you can trust.



¹ Max at 12VDC

² 12-24VAC not available with 2364 model

³ Fire-rated (F) model only. 3-hour for single swing, 90 minutes for standard pair of doors.

bestaccess.com

dormakaba

BEST is a trademark of dormakaba USA Inc. All rights reserved.



BA-0336

© 2018 dormakaba USA Inc.