

# GWZQ.R14283 - Door Hinges

## Door Hinges

[See General Information for Door Hinges](#)

### DORMAKABA USA INC

R14283

6161 E 75TH ST  
PO BOX 50444  
INDIANAPOLIS, IN 46250 USA

Series 600 — Stainless or cold rolled steel continuous hinge for use on swinging-type fire doors rated up to and including 3 hr on single doors up to 48 in. in width by 120 in. in height or door pairs up to 96 in. in width by 120 in. in height.

**Full mortise, butt hinges**, 3-Knuckle (concealed bearing) and 5-Knuckle (ball bearing and concealed bearing) Stanley Security Standard Weight Series for use on swinging-type fire doors rated up to and including 3 hr.

3-Knuckle (concealed bearing) and 5-Knuckle (ball bearing and concealed bearing) Stanley Security Heavy Weight Series for use on swinging-type fire doors rated up to and including 3 hr on single doors up to 48 in. in width by 120 in. in height or door pairs up to 96 in. in width by 120 in. in height.

**Half mortise, butt hinges**, 3-Knuckle (concealed bearing) and 5-Knuckle (ball bearing and concealed bearing) Stanley Security Standard Weight Series for use on swinging-type fire doors rated up to and including 3 hr.

3-Knuckle (concealed bearing) and 5-Knuckle (ball bearing and concealed bearing) Stanley Security Heavy Weight Series for use on swinging-type on single doors up to 48 in. in width by 120 in. in height or door pairs up to 96 in. in width by 120 in. in height.

**Half surface, butt hinges**, 3-Knuckle (concealed bearing) and 5-Knuckle (ball bearing and concealed bearing) Stanley Security Standard Weight Series for use on swinging-type fire doors rated up to and including 3 hr.

3-Knuckle (concealed bearing) and 5-Knuckle (ball bearing and concealed bearing) Stanley Security Heavy Weight Series for use on swinging-type fire doors rated up to and including 3 hr on single doors up to 48 in. in width by 120 in. in height or door pairs up to 96 in. in width by 120 in. in height.

**Continuous hinges**, Series 661, 661WT, 666, 666WT, 668, 665, 674, 675, 662, 671, 672, 673, 676, 677, 678, 663, 679, 664, 680 (may be suffixed with DD, PT, ES, EC, M, R, TW2, TW4, TW8, TW12, AMS, ADB, MM, MT2, MT4, MT8, HT, EZ4, EZ8, EZ12, SL, WT, SC, 79"). Aluminum continuous hinge for use on wood and metal swinging type fire doors rated up to and including 1 hr without interlocking pins, metal swinging type fire doors rated up to and including 1-1/2 hr without interlocking pins, wood swinging type fire doors rated up to and included 1-1/2 hr when supplied with interlocking pins, and metal swinging type fire doors rated up to and including 3 hr when supplied with interlocking pins.

Trademark and/or Tradename:



[Last Updated](#) on 2019-03-26

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"